

APC Online 10kVA

Introducing state of the art, Next Gen Online UPS

SRC10KUXI



- 1 >94% efficiency (double-conversion mode)
Save Rs 20k every year*
Save even more in Green mode, 98% efficiency
- 2 3ph or 1ph input (site configurable)
- 3 0.9 power factor (9kW output)
- 4 Separate Bypass input allows “Hot Standby” operation
- 5 High-Power Charger: 3kW max
- 6 SMF/Tubular battery selectable
- 7 40-70Hz input frequency range
- 8 Graphical LCD easy-to-use interface
- 9 192V battery, single string
- 10 SmartSlot for all management card options
- 11 EPO, USB, RS232C, Dry Contacts
- 12 Rack/Tower convertible, 3U in rack
- 13 Air filter: User maintain-able

Product feature	SRC10KUXI
Input Specifications	
Nominal Input Voltage	230V (1P); 400V (3P+Neutral)
Input Frequency	40-70 Hz
Input Voltage	100-285 V (1P) 173-494 V (3P)
Input Power Factor	0.98
Output Specifications	
Output Power Capacity	9000 W / 10000 VA
Nominal Output Voltage	230 V
Other Programmable Volt	220 v / 240 V
Efficiency at full load	> 94% in Online mode > 98% in green mode .
Waveform	Sinewave
Bypass Specifications	
Bypass Type	Internal Static Bypass (automatic & manual), Opt. External Bypass
Bypass Input Voltage	170 V – 270V
Max Bypass Current	70 A
Input Protection	Circuit Breaker
Battery Charger Specifications	
Supported Battery Types	SMF / VRLA / Flooded
Battery Bank Voltage	192 V
Max Power Current	3000 W / 13 A
Environmental Specifications	
Operating Temp	0 – 50°C
Storage Temp	-15°C to 60°C
Operating Elevation	1000m without derating
Storage Elevation	15000m
Humidity	0 to 95% RH, non-condensing
Physical Specifications	
Dimensions without pack	13.4cm (W) x 43.3cm (H) x 70.6cm (D)
Dimensions with packing	27.5cm (W) x 57cm (H) x 79cm (D)
Weight without packing	27.5 kg
Weight with packing	32 kg

Accessories

PDU

AP7520 offers much needed sockets for a true rack mounting solution

- 9.2kW total load capacity
 - 4 nos. C13 outlets
 - 4 nos. C19 outlets
 - Thermal overload protection
 - Rack / wall mounting
 - 1U Rack height
 - Can be mounted behind battery pack
- SRC192XLBP-IN



Rackmount Battery Pack

For truly rackmount solution APC introduces SRC192XLBP-IN. You can attach upto 4 units of this battery pack to scale up runtime as per your needs. All truly plug and play.

- Rackmountable in standard rack
- Rack/Tower configuration
- Daisy chain upto 4 battery packs for scalable runtime



Accessories

Accessory Cards & others

Choose from a host of Smart slot cards and other accessories to monitor environment and control devices connected to your UPS.

- AP9335TH : APC Temperature and Humidity Sensor
- APC9630 : APC UPS Network Management Card 2
- AP9631 : APC UPS NMC Card 2 with Environmental monitoring
- AP9810 : APC dry contact I/O accessory
- AP9613 : APC Dry contact I/O Smart Slot Card
- AP9624 : APC UPS Interface expander 2



Schneider Electric IT Business India Pvt. Ltd.
4th Floor, Electra, Wing 'A'
Prestige Tech Park
Exora Business parks
Marathahalli,
Sarjapur Outer Ring Road,
Bangalore - 560 103
Ph : +91 80 4333 3333
customercare@apcc.com

APC[®]
by Schneider Electric